



Under mount brackets included



The APS401R is a parking sensor system designed specifically for commercial vehicles requiring either front/rear steel bumper or under mount installation. The LED display with audible alert assists you with distance guidance. The APS401R also has a wide 9-32V DC input, making it suitable for a variety of vehicles.

APS401R

12/24V PARKING SENSOR SYSTEM

SPECIFICATIONS

GENERAL

- Rated Voltage: 12/24V DC
- Operating Range: 9-32V DC
- Operating Current: 20~150mA @ 12V

LED/BUZZER

- Proximity Alert: Visual & Audible Tone
- Audible Buzzer: 70~90dB @ 10cm
- Cable Length: 8m (LED display)

CONTROL BOX

- Adjustments: DIP Switch 1 - Front or Rear Use
DIP Switch 2 - Front Range Select / Tow Bar Adjustments
- Front Setting: Speed Setting Adjustment
- Front Setting: Auto On/Off with Brake
- Power Leads: 4.5m
- Dimensions: 100 x 54 x 24mm

SENSORS

- Sensor Type: Angled Rubber
- Sensor Size: 20mm
- Sensor Hole Cut-out: 18.8mm
- Sensor Cable Length: 3.5m
- Sensor Installation: Under Mount or In-Bumper Mount
Front: =400~500mm High
Rear: =500~600mm High
Front setting: 0.3~0.9m
Rear setting: 0.3~2.5m
- Detecting Distance: -30° to +85°C
- Working Temperature: IP68
- Water Resistance: 26W x 26H x 23.8Dmm
- Sensor Dimensions: 61W x 31H x 22.4Dmm
- Under Mount Dimensions:

INCLUDES

- 1x Control Box
- 4x Sensor
- 4x Under mount brackets
- 1x LED display
- 1x Power cable
- 1x 21mm Hole Saw
- 1x Accessories



System



Display



18mm Sensors



Surface & Under Mount



Front or Rear



9 321886 016291