

## MOBILE NETWORK REPEATER ANTENNAS









The BOOST Mobile Network Antennas have been expertly calibrated to enhance the frequencies required in conjunction with a signal booster, resulting in an exceptional connection in regional areas where signal strength is weak. This allows for the most optimal performance possible.

## **SPECIFICATIONS**

 Optimized Bands: N5. N8. N28 Horizontal Beamwidth: Omni-Directional

· Polarisation: Vertical

· Maximum Gain:

4.1dBi BOOST-M600: 5dBi BOOST-M1000: 5dBi BOOST-L900:

· Overall Height:

BOOST-M600: 600mm BOOST-M1000: 1000mm BOOST-L900: 900mm

· Whip Type: Detachable Collinear

· Whip Material: Fibreglass

· Whip Diameter:

Ø 23mm BOOST-M600: BOOST-M1000: Ø 23mm BOOST-L900: Ø 16mm Stainless Steel · Spring:

· Spring Diameter:

BOOST-M600: Ø 45mm BOOST-M1000: Ø 45mm BOOST-L900: Ø 25mm

4.5m LMR240 COAX Cable: · Cable Terminated: SMA male connector





AUTOBACS AUSTRALIA PTY LTD www.autobacs.com.au

**2**YEAR WARRANTY

## **INCLUDED**

SMA/F to FME/F Adaptor

**0081-M1000** 



