

HIGH RESOLUTION CAMERA KITS

HD5120K
AVAILABLE



HD7130K

12/24V
POWER


TOUCH SENSITIVE
BUTTONS


PARKING GUIDELINES

3
CAMERA INPUTS
7 INCH

2
CAMERA INPUTS
5 INCH

IP68
CAMERA

7" & 5" MONITOR SPECIFICATIONS

- TFT Panel: New Grade A LCD
- LCD Size: 7-Inch Diagonal (5- inch available)
- Display Format: 16:9
- Resolution: 7" & 5" (1024 x 600)
- Brightness: < 500 CD/M²
- Viewing Angles: 70° Left/Right/Up/Down
- Video System: Auto PAL/NTSC Select
- Video Connect: 7" (3 x 4-Pin Male)
5" (2 x 4-Pin Male)
- Camera Triggers: 7" (3 - CAM 1, CAM 2 & CAM3)
5" (2 - CAM 1 & CAM 2)
- Monitor View: Normal/Mirror/Flip/Mirror-Flip Image Select
- Buttons: Touch Sensitive
- Guidelines: Selectable On/Off
- Audio: Built-in
- Operating Temp: -20°C to +70°C
- Power Input: 10-32V DC (Negative Ground)
- Dimensions: 7" (179W x 122H x 28Dmm excluding bracket)
5" (132.2W x 94.3H x 22.45Dmm excluding bracket)
- Operating Temp: -20°C ~ +60°C

CAMERA SPECIFICATIONS

- Image Device: 1/2.9" PV4209K
- Diagonal Viewing Angle: 120°
- Horizontal Viewing Angle: 103°
- Signal System: PAL
- Effective Pixels: 1920(H) x 1080(V)
- Resolution: 1080P
- Compatibility: High Resolution HD Series Monitors
- Sync System: Internal
- Orientation: Mirror Image
- Night Vision: 4 Infrared LED's
- Illumination: 0.01 Lux with IR on
- Ingress Protection: IP68
- Integrated Microphone: Yes
- Operating Temp: -20 to 70° C
- Dimensions (Excl. Bracket): 77.2W x 48.2H x 65.2D mm
- Connection: Universal Standard 4-Pin Female
- Power Supply: 12V DC (9-16V)
- Power Consumption: <3W
- Max Current: <250mA

INCLUDED IN THE BOX

Monitor & Camera
U-Shape Bracket & Gymbal Knobs
Sun Shade
Power/Camera/Trigger Harness
15M Camera Lead

3 YEAR WARRANTY



AUTOBACS AUSTRALIA PTY LTD
www.autobacs.com.au

HD7130K



9 321886 016062

HD5120K



9 321886 015362