



FUJISERIES

HIGH RESOLUTION
REVERSE MONITORING



HIGH RESOLUTION CAMERA KITS



HD7130K

12/24V
POWER


TOUCH SENSITIVE
BUTTONS


PARKING GUIDELINES

3
CAMERA INPUTS
7 INCH

IP68
CAMERA

7" MONITOR SPECIFICATIONS

- TFT Panel: New Grade A LCD
- LCD Size: 7-Inch Diagonal
- Display Format: 16:9
- Resolution: (1024 x 600)
- Brightness: < 500 CD/M²
- Viewing Angles: 70° Left/Right/Up/Down
- Video System: Auto PAL/NTSC Select
- Video Connect: (3 x 4-Pin Male)
- Camera Triggers: (3 - CAM 1, CAM 2 & CAM3)
- Monitor View: Normal/Mirror/Flip/Mirror-Flip Image Select
- Buttons: Touch Sensitive
- Guidelines: Selectable On/Off
- Audio: Built-in
- Operating Temp: -20°C to +70°C
- Power Input: 10-32V DC (Negative Ground)
- Dimensions: (179W x 122H x 28Dmm excluding bracket)
- Operating Temp: -20°C ~ +60°C

CAMERA SPECIFICATIONS

- Image Device: 1/3" IMX225LQR-C
- Diagonal Viewing Angle: 105°
- Horizontal Viewing Angle: 85°
- Signal System: PAL
- Effective Pixels: 1280H x 720V
- Resolution: 720p
- Sync System: Internal
- Orientation: Mirror Image
- Night Vision: 18 Infrared LED's
- Illumination: 0.01 Lux with IR on
- Ingress Protection: IP68
- Integrated Microphone: Yes
- Operating Temp: -20 to 70° C
- Power Consumption: 3W, 250mA
- Dimensions: 98.3W x 67.7H x 68D mm (including Bracket)
- Connection: Terminated 4-Pin Female
- Power Supply: 12V DC

INCLUDED IN THE BOX

Monitor & Camera
U-Shape Bracket & Gymbal Knobs
Sun Shade
Power/Camera/Trigger Harness
15M Camera Lead

3 YEAR WARRANTY

HD7130K



9 321886 016062