



7 INCH HIGH RESOLUTION DVR WIRELESS SYSTEM

# HDVR74W



12/24V



IP69K  
CAMERA



QUAD  
VIEW



DVR  
RECORDING

The HDVR74W is a complete wireless reversing system that enhances driving safety. With its high-resolution 7-inch display, top of the line camera with audio capabilities, and quad view functionality that can accommodate up to 4 cameras, this system provides complete visibility of the vehicle's surroundings, making it easier to manoeuvre and park the vehicle safely. The system is equipped with DVR recording functionality, allowing drivers to record video footage of their entire journey, providing a complete record of any incidents or accidents that may have occurred.



## SPECIFICATIONS

### MONITOR

|                              |   |
|------------------------------|---|
| • TFT Panel:                 | LCD   |
| • LCD Size:                  | 178mm (7-Inch) Diagonal                     |
| • Display Format:            | 16:9  |
| • Resolution:                | 1024 x 600                                  |
| • Contrast:                  | 700:1                                       |
| • Brightness:                | 600cd/m <sup>2</sup>                        |
| • Video Connect:             | Up to 4 Wireless Cameras                    |
| • Viewing Angles:            | 85° (Left/Right/Up/Down)                    |
| • Split Screen:              | Single/Dual/Quad Selectable Display         |
| • Monitor View:              | Normal/Mirror/Flip/Mirror-Flip Image Select |
| • Screen Dimmer:             | Automatic or Manual Adjustment              |
| • Guidelines:                | Adjustable Size & Position                  |
| • DVR Recording:             | Monitor Displayed Vision                    |
| • Recording Media:           | Micro SD Card: 128 GB Max (Not Included)    |
| • Operating Frequency:       | 2400 -2483.5MHz                             |
| • Receiving Sensitivity:     | -78dBm                                      |
| • Decompression Format:      | H.264 (MP4)                                 |
| • Time Delay:                | 200 ms                                      |
| • Audio Output:              | Built-in 1.5W                               |
| • Operating Voltage:         | 10-32V DC (Negative Ground)                 |
| • Backup:                    | Super Capacitor                             |
| • Power Consumption:         | 10W Max                                     |
| • Operating Temperature:     | -20~+70°C, RH90%                            |
| • Storage Temperature:       | -30~+80°C, RH90%                            |
| • Dimensions (Monitor Only): | 183W x 131H x 30D mm                        |
| - Storage Temperature:       | -30~+80°C, RH90%                            |
| - Dimensions (Monitor Only): | 183W x 131H x 30D mm                        |

### CAMERA

|                             |                             |
|-----------------------------|-----------------------------|
| • Image Sensor:             | 1/2.9" CMOS                 |
| • Effective Pixels:         | 1920 x 1080                 |
| • Viewing Angle:            | 130° Diagonal               |
| • S/N Ratio:                | 38dB                        |
| • Dynamic Range:            | 81dB                        |
| • Transmitter Power:        | 20dBm                       |
| • Bit Rate:                 | 12Mbps                      |
| • Ingress Protection:IP69K  |                             |
| • Minimum Illumination:     | 0 Lux (4 IR LEDs)           |
| • Operating Frequency:      | 2403MHz-2478MHz             |
| • Modulation:               | FHSS                        |
| • Line of Sight Range:      | 120 metres                  |
| • Microphone:               | Yes                         |
| • Operating Temperature:    | -20~+70°C, RH95%            |
| • Storage Temperature:      | -30~+80°C, RH95%            |
| • Operating Voltage:        | 10-32V DC (Negative Ground) |
| • Power Consumption:        | 4W Max                      |
| • Dimensions (Camera Only): | 80W x 49H x 67D mm          |

### INCLUDED

Monitor, Sunshade, U-Bracket & Thumb Screw Set, Stand Mount, Camera, Camera Mount & Sunshade Wiring Harness, Power Cable, Antenna x2, Patch Antenna, Hex Key x2

Due to improvement in technology and design, specifications are subject to change without notice.  
Product visuals are for illustrative purpose only.  
Made in PRC



9 321886 017489



AUTOBACS AUSTRALIA PTY LTD  
www.autobacs.com.au

3YEAR WARRANTY