



PRO5X-2TP

TWIN 5W UHF LMR/CB HANDHELD PACK
80CH IP54 WATER/DUSTPROOF

The Midland PRO5X-2TP UHF-CB & LMR hybrid is built with a sturdy diecast aluminium chassis and IP54 protection to withstand dust ingress & splashes of water. It offers user friendly controls, excellent audio quality and an assortment of accessories.

SPECIFICATIONS

- Switchable Output Power:	1/2/5w	- Input Power:	DC 7.4V
- Channels:	80CB/128LMR	- Antenna:	50Ω
- Frequency Range:	CB 476.425 ~ 477.4125MHz LMR 450 ~ 520MHz	- Accessories Port:	2-Pin Kenwood Type
- Ingress Protection:	IP54	- Operating Temperature:	-20° ~ +55° C
- Chassis:	Aluminium	- Dimensions (incl. Ant):	234H x 60.5W x 43D mm
- Battery Capacity:	2600mAh Li-Ion	- Weight (including Belt Clip):	261g
- Battery Save:	Yes	- Typical Range (@5W):	15km Line of Sight
- CTSCC Tones:	50		
- DCS Cones:	108	INCLUDES	
- Function Keys:	2	- 2 x PRO5X 5W CB/LMR Handheld Radios	
- Keypad:	Simple	- 2 x MA25LK Waterproof Speaker Mics	
- Display:	Backlit LCD	- 2 x AL15 12V CIG. DTC Charger	
- Monitor:	Yes	- 2 x CA13 Desktop Chargers	
- Dual Watch:	Yes	- 2 x 240V AC Adaptor	
- CH Scan:	Yes	- 1 x Waterproof Rugged Case	
- Key Lock:	Yes	OPTIONAL ACCESSORIES	
- Roger Beep:	Yes	- MA31LK:	Air Tube Earpiece Mic
- Squelch:	Yes	- MA21LK:	Earpiece Mic
- VOX:	Yes	- CA13-4:	4-Bay Desktop Charger
- Channel Width:	12.5KHz (narrowband + wideband)		
- Operation Mode:	Simplex/Duplex		
- Operating Voltage:	7.4V		

LMR
COMMERCIAL READY



12 Volt Charger

Waterproof Carry Case



5 year warranty*

*3 Year Standard Warranty. To claim bonus 2 Year Warranty visit www.midlandaustralia.com.au to register your product.

Due to improvements in technology and design, specifications are subject to change without notice.
Made in China

AUTOBACS
オートバックス