

audioxtra.com.au 2year warranty





SD20 12/24V DUAL MOUNT CAMERA

SPECIFICATIONS

· Image Device: 1/3" CMOS · Diagonal Viewing Angle: 120° · Horizontal Viewing Angle: 100° · Signal System: PAL

· Effective Pixels: 640(H) x 480(V) 480 TV Lines · Resolution: · Compatibility:

All Monitors with RCA Input

· Lens: Full Glass

· Orientation: Selectable Mirror/Non-Mirror

· Guidelines: Selectable On/Off

· Light Sensitivity: 0.2 Lux · Ingress Protection: IP67 · Integrated Microphone: No • Operating Temp: -20 to 70° C • Power Consumption: <1W 20-90mA

16.5W x 16.5H x 23D mm (Excluding Bracket) • Dimensions (Excl. Bracket):

Mini 4-Pin / Terminated RCA (M) · Connection:

· Lead: 6M • Power Supply: 9-32V DC • Power Consumption: <1W Max Current: <90mA

INCLUDED IN THE BOX



SD20



Dual Mounting Heads

Installation Hardware

Metal Hole Saw for Bumper Fit Installaion

6m Video Cable Mini 4Pin to RCA (M)

PACKAGING & PRODUCT INFORMATION





Due to improvements in technology and design, specifications are subject to change without notice. Made in China



AUTOBACS Audioxtra is a subsidiary of the AUTOBACS SEVEN Global Network